



Transvaal Rubber Group



Truco manufactures and supplies a comprehensive range of Small Bore Rubber Hoses that provide long-lasting performance across a variety of applications, from industrial, mining and manufacturing to dairy, food and beverage.

Truco hoses meet and exceed applicable international ISO standards.

Small Bore Rubber Hose



Greenline Industrial Rubber Hose

Greenline Industrial Rubber Hose is a medium-duty air and water hose for medium pressure mining and industrial applications, including pneumatic air tools, portable compressors and various other air and water applications.

- Reinforced with multiple plies of synthetic yarn
- Made from a blend of black NR and synthetic rubber
- Working pressure up to 1 400 kPa
- Temperature range from -20 to 80° C
- Available sizes from 6 to 100 mm in diameter
- Available in 30 m rolls



Goldline Air and Water Rubber Hose

Goldline Air and Water Rubber Hose is suitable for a wide range of high-pressure air and water applications including rock drilling. This robust hose is best suited for use in construction sites and quarries as well as in industrial plants.

- Reinforced with multiple plies of synthetic yarn
- Made from a blend of black NR and synthetic rubber
- Working pressure up to 2 000 kPa
- Temperature range from -20 to 80° C
- Available sizes from 12 to 100 mm in diameter
- Available in 30 m rolls



Rubber Sand and Shotblast Hose

Sand and Shotblast Hose has a highly abrasive-resistant liner that is suitable for conveying sand, shot and other sharp and abrasive particles at high velocities.

- Reinforced with multiple plies of high-tensile synthetic yarn
- Abrasion-resistant NR/SBR liner
- Available sizes: 32 and 38 mm
- Working pressure: 1 000 kPa
- Available in 15 or 30 m rolls



Rubber Suction and Delivery Hose

Truco's Rubber Suction and Delivery Hoses are ideal for the suction and delivery of water and weak acids and alkalis. This hose incorporates a twin high-tensile wire helix embedded into the carcass of the hose that prevents the hose from kinking in small bend radius applications. Oil Suction and Delivery Hoses are also available.

- Reinforced with multiple cords of synthetic yarn and double high-tensile wire helix
- Made from a blend of black NR and synthetic rubber
- Working pressure up to 1 000 kPa
- Temperature range: -20 to 80° C
- Available sizes from 38 to 150 mm in diameter
- Available in 30 m rolls



Oil Resistant Rubber Hose

Oil Resistant Rubber Hose is a multi-purpose hose that is ideal for medium-pressure industrial applications where resistance to heat, oil or oil-based products is required. This hose is able to convey fuels with an aromatic hydrocarbon content not exceeding 50%.

- Reinforced with multiple cords of synthetic yarn
- Made from black NBR compound
- Working pressure up to 1 000 kPa
- Temperature range: -20 to 90° C
- Available sizes from 6 to 50 mm in diameter
- Available in 30 m rolls



Blue Non-marking and Non-conductive Nitrile Hose

Blue Non-marking and Non-conductive Nitrile Hose is used as a washdown hose in dairies, breweries and abattoirs where a non-marking hose is required. This hose can convey petroleum-based products such as oil and LPG. It can also be used for non-conductive applications such as the conveying of cooling water on an electric arc furnace.

- Reinforced with multiple plies of synthetic yarn
- Made from a blue NBR compound
- Working pressure up to 1 000 kPa
- Temperature range: -20 to 90° C
- Available sizes from 12 to 50 mm in diameter
- Available in 30 m rolls
- Not a food grade hose



High Pressure Jackhammer Hose

High Pressure Jackhammer Hose is a robust, heavy-duty, high-pressure air hose suited for tough, arduous environments and rugged mining conditions.

- Reinforced with woven polyester yarn
- Hose is made with a black NR/SBR liner and yellow NR cover
- Working pressure: 2 700 kPa
- Temperature range: -20 to 80° C
- Available size: 25 mm in diameter
- Available in 50 m rolls



Blue Oxygen and Red Acetylene Hose

Blue Oxygen and Red Acetylene Hoses are ideal for gas welding and cutting applications, and are used between gas cylinders and cutting / welding torches. These ISO-approved and marked hoses have burst pressures in excess of 7 000 kPa.

- Reinforced with multiple plies of woven polyester yarn
- Hose is made with a black NR/SBR liner and blue or red NR cover
- Working pressure: 2 000 kPa
- Temperature range: -20 to 80° C
- Available sizes: 5, 6 and 8 mm in diameter
- Available in 100 m rolls



Radiator Hose

Radiator Hose is used to convey most chemicals and glycol-based coolants at elevated temperatures, mainly on radiators or hot water lines. Truco's Radiator Hose provides high strength and long-lasting performance in the toughest conditions.

- Reinforced with multiple plies of synthetic yarn
- Hose is made with a UV-resistant EPDM liner and cover
- Working pressure: 500 kPa
- Temperature range: -20 to 130° C
- Nominal bore sizes: 20 to 115 mm
- Packaged in 1 m lengths



Fuel Line Hose

Fuel Line Hose is ideal for conveying fuel and oil with an aromatic content less than 50%. This hose can also be used in oil applications where oil resistance or oil mist resistance is required, such as in compressed air and pneumatic tool applications.

- Reinforced with multiple plies of synthetic yarn
- Made with a black NBR liner and cover
- Working pressure: 1 000 kPa
- Temperature range: -20 to 130° C
- Available sizes: 6, 8, 10 and 12 mm in diameter